



## Product data sheet

# HAVXS4T5600G6300P

### Characteristics

Variable speed drive, EXPERT-Standard, 560 kW, 380 V, 3 phase, standard



#### Main

Range of product	EXPERT-Standard
Product or component type	Variable speed drive
Product specific application	Advance general purpose
Format of the drive	Standard
Product destination	Asynchronous motors
IP degree of protection	IP20
Type of cooling	Fan
Network number of phases	3 phases
[Us] rated supply voltage	380...440 V - 15...10 %
Motor power kW	560 kW for heavy duty 630 kW for light duty
Motor power hp	750 hp for heavy duty 845 hp for light duty
Maximum transient current	1575 A during 1 min (heavy duty) 1890 A during 3 s (heavy duty) 2100 A during 0 s (heavy duty) 1380 A during 1 min (light duty) 1725 A during 3 s (light duty) 2070 A during 0 s (light duty)
Asynchronous motor control profile SVC and V/f energy saving ratio	
Speed drive output frequency	0...550 Hz
Communication port protocol	Modbus CANopen EtherNet/IP Profibus DP PROFINET DeviceNet EtherCAT

#### Complementary

Device application	Speed control
Function available	Automatic voltage regulation (AVR) Energy saving mode Fixed and variable swing frequency Length control Sagging (multiple inverters drive one load) Multi-speed operation Jogging Adjustable wobble frequency
Supply frequency	50...60 Hz
Maximum voltage unbalance factor	3 %
Continuous output current	1050 A heavy duty 1150 A light duty

Control type	Manual using keypad Using control terminal Using serial port Three way control using output collector terminals
Efficiency	93 %
Communication service	Read motor parameters automatically
Electrical connection	DC bus sharing
Speed range	1...100 in open-loop mode
Speed accuracy	+/- 0.1 % of nominal speed
Regulation loop	Adjustable PID regulator
Acceleration and deceleration ramps	Linear adjustable separately from 0.1 s...60 h S-curve adjustable separately from 0.1 s...60 h
Braking to standstill	By DC injection,
Protection type	Overcurrent Overvoltage Undervoltage Overheating Overload
Protection technology	Current limiter
Frequency resolution	Digital input: 0.01 Hz Analog input: 0.55 Hz
Display type	7 segments LED for 27 parameters
Device mounting	Wall mounted Enclosure Floor mounted
Product compatibility	External braking unit Communication module I/O extension module
Width	950 mm
Height	1812 mm
Depth	490.5 mm
Analogue input number	3
Analogue input type	AI1 voltage: 0...10 V, impedance: 100000 Ohm, resolution 12 bits AI2 current: 0...20 mA, impedance: 165 Ohm, resolution 12 bits AI2 voltage: 0...10 V, impedance: 100000 Ohm, resolution 12 bits AI3 voltage: differential +/- 10 V, resolution 12 bits
Discrete input number	6
Discrete input type	Programmable (DI1...DI5) Programmable as pulse input (DI6)
Analogue output number	1
Analogue output type	AO1 voltage/current: 0...20 mA or 0...10 V AO2 voltage/current: 0...20 mA or 0...10 V
Discrete output number	4
Discrete output type	configurable relay logic 250 V (5 A) for NO relay output circuit configurable relay logic 250 V (3 A) for NC relay output circuit open collector 9...30 V (50 mA)
Type of installation	Indoor/outdoor
Application	Material handling machine Textile machine Material working machine Industrial washing machine Air compressor Construction elevator Metal and mining process Petrochemical



Vibration resistance	5.9 m/s <sup>2</sup>
Relative humidity	0...90 % without condensation
Ambient air temperature for operation	-10...40 °C
Ambient air temperature for storage	-20...60 °C
Operating altitude	
Environmental characteristic	Dust resistant Corrosive gas free Oil and vapour resistant
Marking	CE