Product data sheet
Characteristics

HDW320M203FH5556M
air circuit breaker, HDW3, 2000AF, 2000 A, 3P, fixed horizontal, 6 NO + 6 NC

Main

Range of product	HDW3
Product or component type	Air circuit breaker
Frame size	2000AF
[Icu] ultimate breaking capacity	50 KA at 690 V load 80 kA at 400 V load
[Ics] rated service breaking capacity	40 KA at 690 V 65 kA at 400 V
[Icw] rated short-time withstand current	40 KA at 690 V duration: 1 s 65 kA at 400 V duration: 1 s

Complementary

[In] rated current	2000 A
Poles description	3P
Mounting mode	Fixed
Mounting position	Horizontal
Voltage release type	Without motor mechanism, closing release, shunt release and undervoltage release
Maximum tripping time	25 ms
Maximum closing response time	70 ms
Auxiliary contact composition	6 NO + 6 NC
Product compatibility	Series intelligent controller iTR326A standard protection
Height	397 mm
Width	364 mm
Depth	327 mm
Net weight	41.4 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.