Product data sheet
Characteristics

HDW332M254FH5556H
air circuit breaker, HDW3, 3200AF, 2500 A, 4P, fixed horizontal, 6 NO + 6 NC

Main

Range of product	HDW3
Product or component type	Air circuit breaker
Frame size	3200AF
[Icu] ultimate breaking capacity	80 KA at 400 V load 65 kA at 690 V load
[Ics] rated service breaking capacity	65 KA at 400 V 50 kA at 690 V
[Icw] rated short-time withstand current	65 KA at 400 V duration: 1 s 50 kA at 690 V duration: 1 s

Complementary

[In] rated current	2500 A
Poles description	4P
Mounting mode	Fixed
Mounting position	Horizontal
Voltage release type	Without motor mechanism, closing release, shunt release and undervoltage release
Maximum tripping time	25 ms
Maximum closing response time	70 ms
Auxiliary contact composition	6 NO + 6 NC
Product compatibility	Series intelligent controller iTR326H advance protection
Height	397 mm
Width	543 mm
Depth	327 mm
Net weight	68 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.